

08 04-08

A

08/03/00
10096 U.S. PTO

JC973 U.S. PTO
09/03/00
09/03/00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Attorney's Docket No. ICB-0027

In re Application of:
Christophe Berthaud

Serial No. Unknown

Filed: Concurrently herewith

Art Unit: Unknown

Examiner: Unknown

For: WATCH INCLUDING A CONTACTLESS CONTROL DEVICE FOR A
COMPUTER CURSOR

NEW APPLICATION TRANSMITTAL LETTER

BOX PATENT APPLICATION
Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

Enclosed for filing is an Application for Letters Patent (consisting of 7 pages of specification, 2 pages of claims, 1 page of abstract and 3 sheets of informal drawing); a Declaration/Power of Attorney form (consisting of 2 pages); Prior Art Statement (consisting of 1 page); Information Disclosure Statement with attached prior art (1 page with references attached); European Search Report of Application Number EP 99 11 6617 with translation and Instructions as to Underpayment/Overpayment of Fees (1 page); and a postcard for "receive" date stamping.

CERTIFICATE OF MAILING

I hereby certify that this New Application Transmittal Letter and all documents referred to as being enclosed or attached is being deposited with the United States Postal Service, "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated below and is addressed to: **BOXPATENT APPLICATION, Assistant Commissioner for Patents, Washington, D.C. 20231.**

EE 877 339 931 US

August 3, 2000

"Express Mail" mailing No. Date of Deposit

RACHEL P. BONVILLAIN

Typed Name of Depositing Person

Rachel P. Bonvillain
Signature of Depositing Person


The application is for a WATCH INCLUDING A CONTACTLESS CONTROL DEVICE FOR COMPUTER CURSOR.

Also, enclosed is a check in the amount of \$690.00 as payment for the Application Filing Fee (18 total claims with 1 independent claim).

The Commissioner is hereby authorized to charge any fee deficiency or credit any fee overpayment relating to the filing of the above-referenced Patent Application and all documents relating thereto to: Deposit Account No. 18-1680.

Respectfully submitted,

Date: August 3, 2000



Richard K. Robinson (PTO Reg. No. 28,109)
Harry C. Post, III (PTO Reg. No. 26,019)
Attorneys for Applicant

Robinson & Post, L.L.P.
North Dallas Bank Tower, Suite 1200
12900 Preston Road, LB-41
Dallas, Texas 75230
Tel: 972-866-7786
Fax: 972-866-7787

WATCH INCLUDING A CONTACTLESS CONTROL
DEVICE FOR A COMPUTER CURSOR

The present invention relates to a watch associated with a control device for a computer cursor. In other words, the present invention proposes integrating in a watch a device which is equivalent to a contactless computer mouse, i.e. without any cabled communication between the watch and the computer. Such communication is known

- 5 to those skilled in the art who may, in particular, use communication via electromagnetic waves, ultrasound or infrared waves.

- A portable contactless interface device used as a computer mouse is known from International Patent No. WO 96/34333. In its preferred described embodiment, this document proposes integrating this interface device between a user and the
- 10 computer in a ring. In its top portion, the ring includes a first protruding part forming a housing for an electronic circuit and including at its surface a directional antenna. In the front lateral portion there is a second protruding part in which is arranged a two dimensional force sensor used to actuate a computer cursor. Moreover, another force sensor is provided in the bottom portion to select objects on the screen or to carry out
- 15 commands relating to these objects. Such an action is referred to hereinafter as a "click". With reference to Figures 2 and 3 and the corresponding description of this document, it is clear that the sensor provided for moving the computer cursor is formed by a two dimensional force sensor actuated by the user's thumb. This force sensor allows the cursor to be moved along two perpendicular directions shown in
- 20 Figure 2. The force sensor thus determines in which of the four directions given in Figure 2 the thumb force is exerted in the plane of the sensor. It will be noted that such a force sensor for actuating a cursor firstly limits the precision of the cursor's movement and it is not easy to use given that the ring undergoes movement on the finger, the skin of the finger experiencing relatively significant movements. Thus, a
- 25 mechanical stress is exerted on the finger and the ring moves when a force is applied by the thumb in one of directions of the sensor plane. It is thus clear that control of the cursor is hampered by these movements of the ring and that this is also uncomfortable for the user.

- As an alternative which may be envisaged, International Patent No.
- 30 WO 96/34333 mentions that it is possible to arrange adjacent sensors on the ring in place of the two dimensional force sensor so that the direction of movement of the cursor is determined by the sequential actuation of the adjacent sensors. This unclear and largely insufficient teaching does not enable those skilled in the art to understand how to make these adjacent sensors and how to use them to control a computer
- 35 cursor properly. Moreover, the small dimensions of the ring shown in this document

seem greatly to compromise such an embodiment. Those skilled in the art may find in US Patent No. 5,481,265 a similar device wherein a member is provided which can be actuated by the thumb to control a computer cursor along two orthogonal directions. This member includes four independent regions forming four adjacent force sensors which may be actuated in succession by the thumb to move the cursor up, to the right, down or to the left. According to a variant, these four pressure sensors allow the cursor to be moved to one of the four corners of the computer screen (see Figures 7a and 12). This device is not at all easy to use given the position required for the thumb. Moreover, the selective application of a force on the four aforementioned pressure sensors is not easy, and is even impaired. Thus, control of the cursor's movement is approximate and in any case limited as is clear from the description of US Patent No. 5,481,265.

The present invention proposes overcoming the drawbacks mentioned relative to the two documents cited above by providing a watch-mouse as defined in claim 1. A watch is an object which is worn on the wrist and may have a relatively large surface area in a conventional embodiment. Generally, most of the top surface of a watch is occupied by the display means. The present invention is characterised in that the outer element forming the crystal protecting the display means or an outer portion of a display cell, in particular an LCD display, is used as support means for the touch sensitive pads which allow a computer cursor to be controlled easily and precisely.

Moreover, various means are provided allowing one or more clicks to be made to select an object shown on the computer screen or to carry out a command relating to such an object. In order to do this, a conventional push-button is used arranged either in a lateral portion of the case, or in the top portion surrounding the watch crystal.

Thus, the watch according to the invention acts as interface for moving a computer cursor and carrying out various commands while keeping a conventional shape and a conventional aesthetic appearance. This latter aspect is not an indispensable feature of the present invention but contributes to demonstrating that the present solution is particularly advantageous compared to the embodiments of the prior art discussed above. The watch-mouse according to the invention may be worn all day long without the computer control linked function having any effect on the aesthetic appearance and the conventional dimensions of the watch.

As a result of the present invention, a user has available a portable contactless control interface, which has a relatively large sensitive zone for his finger. Touch sensitive sensors, in particular capacitive or resistive sensors, unlike force sensors, do not require the application of relatively significant pressure. Consequently, the

mechanical stress exerted on the watch is negligible and this watch does not undergo any significant movement on the user's arm. Thus, it is easy to use and allows precise and efficient control of a computer cursor.

Other advantages of the present invention will also become clear from the following description of various embodiments, given by way of non-limiting example, which are shown on the annexed drawings in which:

- Figure 1 is a schematic top view of a first embodiment of the invention;
- Figures 2 and 3 are respectively two graphs showing the movement of the cursor on the screen relative to the movement of the finger on the sensitive zone defined by the touch sensitive sensors;
- Figure 4 is a schematic top view of a second embodiment of the invention;
- Figure 5 is a schematic top view of a third embodiment of the invention;
- Figure 6 is a schematic top view of a fourth embodiment of the invention; and
- Figure 7 is a cross-section of Figure 6 along the line VII-VII.

Figure 1 shows a watch 1 including a case 2 and a crystal 4 covering an analogue display comprising two hands 8 and 10 shown in dotted lines. Next, watch 1 includes a crown 12 and a push-button 14 approximately located between 7 and 8 o'clock.

According to the invention, watch 1 includes means for controlling the movement of a computer cursor formed by a set of touch sensitive sensors whose sensitive pads 16 are carried by crystal 4. More precisely, in the present embodiment, the touch sensitive sensors are of the capacitive type and sensitive pads 16 are formed by electrodes deposited underneath crystal 4 (see Figure 7). Each electrode is electrically connected to an electronic unit for processing the received signals, in particular using contact pads located on the periphery of crystal 4, and connected to this electronic unit by a connector formed of a succession of alternately conducting and insulating sections. Those skilled in the art know how to form transparent electrodes at the surface of a glass and how to connect a plurality of capacitive touch sensitive sensors to an electronic unit (not shown) located inside watch 1. As crystal 4 occupies most of the top surface of case 2, the sensitive zone for actuating a computer cursor is relatively large without the conventional dimensions of a watch being modified, nor the external appearance nor the time display in analogue form. It will be noted however that the invention also applies to a digital time display. In this latter case, sensitive pads 16 of the capacitive sensors are arranged either on a protective glass covering the LCD cell, or at least partially on the top portion of the LCD cell.

The set of sensitive pads 16 is supported by crystal 4 and these pads extend over most of the crystal. In an alternative embodiment, part of the sensitive pads of the touch sensitive sensors may be located on the bezel or top portion 18 of case 2.

Sensitive pads 16 define the touch-sensitive zone of the watch for actuating the movement of a computer cursor. In Figure 1, these sensitive pads 16 are arranged in the shape of a matrix defining substantially square pad lines and columns.

In a first cursor control variant, it is possible to determine the set of sensitive pads actuated when a finger passes over crystal 4. Then, via a known method, in particular that of least squares, a corresponding direction of movement is defined for the cursor. Moreover, the speed at which the successive sensitive pads are actuated allows a speed of movement to be determined for the cursor, which is for example proportional to the speed of movement of the finger over the crystal. By differentiating the level of actuation of each touch sensitive sensor, it is possible to perform a weighting in the linear regression suggested hereinbefore. Moreover, it is possible to decompose the movement of the finger by performing a linear regression by sector or region of the touch-sensitive zone.

According to a second cursor control variant, the path of the finger across crystal 4 is traced and a cursor movement corresponding to this path is reproduced with a given amplification factor. In order to do this, one can, in particular, select the sensitive pads actuated above a certain threshold or only retain in each predetermined time period the touch sensitive sensor having the maximum level of actuation or the centre of gravity of the sensors all having substantially such a maximum level. One may thus determine with a given frequency the successive positions of a finger over crystal 4. Moreover, it is then easy to determine a speed of movement of the finger.

According to an improved cursor control variant, the movement of the cursor on the screen is varied in a non linear manner as a function of the movement of the user's finger over the sensitive zone of the watch. According to a first implementation represented by the graph in Figure 2, the ratio between movement ΔY of the cursor and the path ΔX taken by the finger over crystal 4 increases as a function of the speed V of movement of the finger over crystal 4 or, similarly, the instantaneous or average frequency F at which the successive actuation of adjacent pads is carried out. In Figure 2, the variation in the aforementioned ratio is continuous as a function of $V(F)$. In a second implementation represented by the graph of Figure 3, the aforementioned ratio is in steps. At low speed, a ratio of 1 is provided. For an average speed a ratio 2 is provided, while for a high speed the ratio is equal to 3. Of course, these values are given by way of non limiting example. As is clear from Figure 2, it is possible for the ratio to be less than 1 for low speeds. This improvement allows large movements to be

made with relative precision when the cursor is far from the target object. Conversely, when the cursor has to be moved precisely over a minimum distance, the present solution allows a small precise movement of the cursor to be made corresponding to the movement of the finger in the general plane by crystal 4.

- 5 Push-button 14 is provided in particular in order to perform the click or double click suited to the operation of a computer mouse. The means for detecting the speed of the finger movement or the actuation frequency of the successive sensor may be imagined by those skilled in the art without any major difficulty. In a conventional manner, push-button 14 is associated with an electric contactor arranged in case 2.
- 10 According to another embodiment, the click function is performed by means of a contactor whose actuation element is located in the top portion of case 2, particularly in the 6 o'clock region. By way of variant, this contactor may be replaced by a pressure sensor or a touch sensitive sensor arranged in this same region. Such embodiments are particularly advantageous because they allow the cursor movement to be
- 15 controlled using the index or middle finger and the click function to be performed using the thumb of the same hand.

- With reference to Figure 4, a second embodiment will be described. The references already described above will not be described again in detail. Watch 21 includes touch sensitive sensors whose sensitive pads 16 of one part are located
- 20 substantially in the peripheral region of crystal 4 and the second part of sensitive pads 17 are arranged on the top portion of case 2. Sensitive pads 16 and 17 form respectively two concentric touch-sensitive zones. In each of these zones, the sensitive pads are arranged in a circle and define relative to centre 24 of these zones, identical to the axis of hands 8 and 10, a variable angular direction. According to this
- 25 second embodiment, the direction of movement of the computer cursor is determined by the orientation of the sensitive pad 16, 17, respectively the sensitive pads 16 and/or 17 actuated by the user's finger relative to centre 24. Further, the speed of the cursor's movement depends on the sensitive zone actuated or two adjacent simultaneously actuated sensitive zones. In the example of Figure 4, three different movement speeds
- 30 can thus be defined, namely, a first speed when only the inner annular zone is actuated, a second speed when the outer annular zone is actuated and a third intermediate speed when the two sensitive zones 16 and 17 are simultaneously actuated. This embodiment is advantageous because the two concentric sensitive zones are materially and visually separated from each other, the inner zone being
- 35 supported by crystal 4 while the outer zone is supported by top portion 18 of case 2 surrounding the crystal. According to a variant shown in Figure 4, the click function is performed by means of a capacitive sensor 26 supported by crystal 4 and located in

the central region thereof. This allows the click function to be performed rapidly using the finger which is also actuating sensitive pads 16 and/or 17. Of course, in order to move the cursor while keeping sensor 26 in an activated state, it is possible to use two fingers. It will be noted here by way of variant that the click function may, in an alternative embodiment, be performed using a push-button as in the case of Figure 1.

In a similar manner to the second embodiment described above, the touch sensitive sensors are arranged in the shape of concentric circular zones in the third embodiment of Figure 5. A part of sensitive pads 16A of these touch sensitive sensors define an inner zone while the sensitive pads 16B of the other part define an outer sensitive zone. However, in the present case, the set of sensitive pads is supported by crystal 4 which is at least partially transparent. A digital display is provided for the time and possibly other data, in particular in zone 34. Since the display itself is not the object of the present invention, this aspect is shown in an entirely schematic way. Crystal 4 may cover the LCD display cell or form a top outer portion of the cell. The control of the cursor's movement is similar to that of the second embodiment. In order to allow the two touch-sensitive zones to be identified, it is possible to provide visual means, in particular a design defining these two concentric zones.

The click function is performed using a member 36 located in a 6 o'clock position and associated with a contactor or switch. By way of variant, member 36 may be associated with a pressure sensor.

According to an alternative embodiment which may also apply to the other embodiments described above, the click function may be achieved by means of a touch sensitive sensor, a pressure sensor or a push-button associated with a contactor arranged in a link 38 of watch wristband 39.

Figures 6 and 7 show schematically a fourth embodiment of a watch according to the invention. The references already described in Figure 1 will not be mentioned in detail again here. The cursor movement control means are similar to the first embodiment. The touch-sensitive zone is located on crystal 4. This fourth embodiment is essentially distinguished by the means allowing the click function to be performed. These means are formed by crystal 4 associated with a pressure sensor, in particular a piezoelectric crystal 44 arranged under crystal 4 in its peripheral region. The click function is performed by applying pressure onto crystal 4.

Sensitive pads 16 are formed by a transparent material and are electrically connected to contact pads 46 located in the peripheral region of crystal 4. These pads 46 are electrically connected to electronic movement 48 and more particularly to electronic processing unit 50 for the electric signals provided by the touch sensitive sensors. This electric connection is achieved using a Zebra® type connector 52

having conducting sections placed facing pads 46, these conducting sections being separated by insulating sections. Such elastomeric connectors are known to those skilled in the art.

Electronic unit 50 is electrically connected to antenna 54 which has contactless communication with a reader or receiver provided in the computer or as a peripheral unit thereof. A battery or rechargeable accumulator 56 is provided as electric power source. It will be noted that the rechargeable accumulator may advantageously be associated with an electric generator integrated in watch 41 and mechanically coupled to an oscillating mass, this system being known to those skilled in the art.

Thus, in this last embodiment, all the functions relating to the control of a computer cursor are associated with crystal 4. The click and double click functions are performed respectively by one application of pressure and two successive applications of pressure on crystal 4. It will also be noted that piezoelectric sensor 44 may have an annular shape or be formed of several segments arranged in a circle. Likewise, connector 52 may be annular or be formed by several segments. In one particular embodiment, the segments forming sensor 44 and the segments forming connector 52 are arranged in a circle in alternance so as to limit the peripheral surface of crystal 4 necessary for the pressure sensor and the electric connector. The pressure sensor may also be formed by piezo-resistive elements or by micro-contactors in another embodiment.

Finally, it will be noted that crystal 4 may have any shape and may, in particular, be substantially square or rectangular.

WHAT IS CLAIMED IS

1. A watch including display means for at one item of time related data and having an at least partially transparent outer element covering said display means or forming an outer portion of these display means, said watch including first control means for controlling the movement of a cursor on a computer screen, said first
5 control means being formed of a plurality of touch sensitive sensors whose respective sensitive pads are supported at least partially by said outer element.

2. A watch according to claim 1, wherein said first means include an analogue display protected by said outer element which defines the watch crystal, said sensitive pads being at least partially superposed with said analogue display.

10 3. A watch according to claim 1 or 2, wherein the set of said sensitive pads of said touch sensitive sensors forming said first means is supported by said outer element.

4. A watch according to claim 1 or 2, wherein a part of said sensitive pads of said touch sensitive sensors is arranged in the top portion of the case of the watch
15 surrounding said outer element.

5. A watch according to claim 1, wherein said respective sensitive pads of said plurality of touch sensitive sensors are arranged in the shape of a matrix defining lines and columns which extend over most of said outer element.

20 6. A watch according to claim 5, wherein it further includes means for detecting the speed of a user's finger over said outer element or the actuation frequency of successive sensors.

7. A watch according to claim 6, wherein the ratio between the movement of said cursor and the path taken by a user's finger across said outer element is less at low speed or actuation frequency than at relatively high speed or actuation
25 frequency.

8. A watch according to claim 5, wherein the movement of said cursor over said computer screen substantially corresponds to the path taken by the user's finger over said outer element.

9. A watch according to claim 1, wherein said sensitive pads are arranged
30 in concentric zones, the direction of movement of said cursor being determined by the orientation of the pad or pads actuated relative to the centre of said concentric zones.

10. A watch according to claim 9, wherein the speed of movement of said cursor depends on the concentric zone actuated or two adjacent concentric zones which are actuated simultaneously.

11. A watch according to claim 1, further including second control means for selecting an object shown on said screen or carrying out a command relating to said object.

12. A watch according to claim 11, wherein said second control means are
5 arranged in the top portion of the case substantially in the 6 o'clock position.

13. A watch according to claim 11, wherein said second control means are also formed by a touch sensitive sensor.

14. A watch according to claim 11, wherein said second control means are formed by a push-button associated with an electric contactor.

10 15. A watch according to claim 11, wherein said second control means are arranged in a link of the wristband of the watch or in a portion of the wristband of the watch.

16. A watch according to claim 11, wherein said second control means are formed by said outer element associated with a pressure sensor, said selection of an
15 object or said command relating to said object being performed by applying pressure onto said outer element.

17. A watch according to claim 16, wherein said pressure sensor is formed by a piezoelectric crystal arranged on the periphery of said outer element.

18. A watch according to claim 11, wherein said second control means are
20 formed by said outer element associated with at least one micro-contactor or small travel contactor.

ABSTRACT

WATCH INCLUDING A CONTACTLESS CONTROL
DEVICE FOR A COMPUTER CURSOR

Watch (1) including time display means (8; 10) covered by a crystal (4). This watch includes an interface device for controlling a computer cursor. It forms a contactless watch-mouse. For this purpose, a plurality of touch sensitive sensors are arranged so that their sensitive pads (16) are supported at least partially by the crystal

5 (4). The sensitive pads are arranged in particular in the shape of a matrix extending over most of the crystal (4). The click function is performed using a push-button (14) associated with electric contactor or by a pressure sensor or by a touch sensitive sensor provided for this purpose.

10 Figure 1




Fig. 1





Fig. 4







Fig. 5




Fig. 6





Fig. 7



PATENT
SOLE
UTILITY

Attorney Docket
No. ICB-0027

DECLARATION AND POWER OF ATTORNEY

I, Christophe Berthaud, the below named inventor, hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled

" WATCH INCLUDING A CONTACTLESS CONTROL DEVICE FOR A COMPUTER CURSOR ",
the specification of which is attached hereto.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to in this declaration.

I acknowledge the duty to disclose to the U.S. Patent Office all information known to me that is material to the patentability of any claim in accordance with Title 37, Code of Federal Regulations, §1.56, and which is material to the examination of this application, namely, information where there is a substantial likelihood that a reasonable examiner would consider it important in deciding whether to allow the application to issue as a patent.

I hereby claim foreign priority benefits under Title 35, United States Code §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

| <u>Country</u> | <u>Application No.</u> | <u>Filing Date</u> <u>(day, month, year)</u> |
|----------------|------------------------|---|
| Europe | 99116617.4 | 25 August 1999 |

I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this

application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

| <u>U.S. Serial No.</u> | <u>U.S. Filing Date</u> | <u>Status</u> |
|------------------------|-------------------------|---------------|
|------------------------|-------------------------|---------------|

POWER OF ATTORNEY

I hereby appoint RICHARD K. ROBINSON (Registration No. 28109, DENNIS T. GRIGGS (Registration No. 27,790) and MICHELLE LARSON (Registration No. 36,193), my attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith. Send all correspondence to:

Richard K. Robinson
Attorney at Law
North Dallas Bank Tower, Suite 1202
12900 Preston Road, LB-41
Dallas, Texas 75230

Direct all telephone calls to Richard K. Robinson at
(972) 866-7786.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of this application or any patent issued thereon.

Full name of inventor: Christophe Berthaud

Residence: Evilard / Switzerland

Citizenship: French

Post Office Address: Chemin des Bourdons 4
CH-2533 Evilard / Switzerland

Date: July 6, 2000 Christophe Berthaud
Christophe Berthaud